

FITNICE

INSTRUCTIONS FOR INSTALLING AND CLEANING FITNICE WALL



FITNICE

INSTALLING INSTRUCTIONS

Carefully read all the instructions before installing the wall covering Fitnice Wall. If the installing instructions are not properly followed the guaranty can be affected, and therefore it is important to totally understand what it is required to start installing the material.

VERIFICATION OF THE SURFACE

The base must be dry, clean, firm, absorbent, flat and with a uniform clarity. It must be completely free of the rests of other recoverings and/or glues used before.

The base must be enough absorbent to allow that the glue can be hit on it to warranty a good adhesion.

In case of extremely absorbent bases (in example, wood) a priming before installing the Fitnice must be made.

In any case, Fitnice recommends the use of a priming before proceeding with the installation of the product. Check the specification of the manufacturer of each priming.

Nevertheless, it is recommended to check the manufacturer's instructions of the glue for each surface.

Before starting the installation of the wall covering Fitnice Wall, we must be sure that there is not humidity or crannies on the zone to be covered, and in case they exist it is recommended to repair them.

Although that there is difference with other wall coverings available in the market, and that Fitnice Wall allows the transpiration of the wall, it is recommended that the wall will be in perfect conditions before the installation.

P.S: in case of bases recently painted, the humidity must be measured with a hydrometer. If this tool is not available and to be able to determine if it is enough dry, the surface can be covered with a plastic film of 50 x 50 cm sealed with adhesive tape for 24 hours. If after this period of time there is humidity under the film, the room must be ventilated or heated to eliminate that excess.



FITNICE

INTALLATION

Preparation of the product

The first thing that must be made is to check that the rolls of Fitnice Wall have the same name of article and the batch, design and colors are the same. It has to be taken into account that to cover the same room the rolls to be used must be of the same batch.

Cut the Fitnice Wall in pieces of a length of additional 5 cm in height to be covered, to compensate possible differences in height. It is recommended to leave resting each piece in a flat surface leaning the inside side part of the Fitnice, during 30 minutes minimum before being installed.

Adhesive Application

It must be put at the top of the wall the reinforced double adhesive tape type (ex. Mapei Adhesive Tape) as a subjection point of each piece.

After that the entire surface where the piece must be installed must be glued. The glue must be applied regularly and directly over the surface using a roller. It is important not to leave lumps or glue excesses, and to avoid that a roller will have to be passed several times on the same zone without adding more glue. In any moment we have to be sure that the quantity of glue is enough to hit but it will not soak the covering.

In case that the Fitnice Wall will be stained with glue, it is recommended to immediately clean using water and alcohol.

Check the time specifications of the manufacturer, but it is recommended to leave 15 minutes before proceeding with the installation of Fitnice Wall. After that, the piece of Fitnice Wall must be put over the humid glued surface and it will have to be pressed with a roller to eliminate bubbles of air and to make sure of the adherence in all over the surface.

The rest of the pieces must be installed following the previous explained process and bearing in mind that they must be installed in a direct joints (edge against edge) and making that the drawing coincides.

At the external edge (opened) it is recommended to apply a stronger ply of glue to guaranty a bigger adherence or to put tape as in the upper part of the installation.

In all the cases it is recommended to install the Fitnice Wall after the painting of the ceiling and other surfaces of the room.

The recommended glues for Fitnice Wall to install it in surfaces of normal absorption (wall, plaster) are:



FITNICE

- Tkrom Mural
- Forbo 565 Mural Plus
- Adesilex MT-32 (MAPEI)

On other surfaces it must be taken in mind the instructions of the glue manufacturers.

CLEANING

The daily use of the product does not require any kind of special cleaning or maintenance. To eliminate rests of dust it can be used a cloth, a duster or a mop often, and from time to time a flannel or wet sponge in a neutral domestic detergent.

In case of special stains, we detail you below how to proceed:

- Liquid stains (coffee, coke, etc...) use a flannel or a wet sponge with water and neutral soap.
- Grease stains (butter, chocolate...) use diluted degreaser. Rinse thoroughly.

In any case try to avoid wetting excessively the covering.

